Newcore Gold Ltd. | Enchi Gold Project

2024 Drill Results

Table accompanies news release dated October 30, 2024



Drill Results Released October 30, 2024

Hole ID	Zone/Deposit	From (m)	To (m)	Length (m)	Au (g/t)	UTM East	UTM North	Elevation	Azimuth °	Dip°	Hole Length (m)
KBRC294	Boin	107.0	113.0	6.0	3.24	519498	634729	125	114	-55	204
including		109.0	110.0	1.0	16.52						
and		120.0	121.0	1.0	0.27						
and		139.0	141.0	2.0	0.35						
and		150.0	204.0	54.0	0.94						
including		151.0	158.0	7.0	2.11						
including		170.0	181.0	11.0	2.08						
KBRC295	Boin	45.0	47.0	2.0	0.34	519533	634699	127	114	-60	157
and		54.0	56.0	2.0	0.31						
and		83.0	91.0	8.0	0.19						
and		113.0	115.0	2.0	0.30						
and		127.0	128.0	1.0	0.97						
and		130.0	154.0	24.0	1.25						
KBRC296	Boin	31.0	56.0	25.0	1.44	519553	634666	125	114	-60	103
and		67.0	74.0	7.0	2.26						
and		90.0	93.0	3.0	0.37						
KBRC297	Boin	0.0	7.0	7.0	0.95	519581	634684	127	114	-60	100
and		12.0	26.0	14.0	0.45						
and		33.0	34.0	1.0	0.22						
and		64.0	68.0	4.0	0.57						
KBRC298	Boin	55.0	67.0	12.0	0.43	519301	634381	130	114	-55	220
and		76.0	78.0	2.0	0.24						
and		154.0	155.0	1.0	0.24						
and		159.0	220.0	61.0	0.53						
and		173.0	185.0	12.0	1.07						

^{1.} Intervals reported are hole lengths with true width estimated to be 75 - 85%.

^{2.} Length-weighted averages from uncut assays.

^{3.} All drilling completed by independent contractor.

^{4.} All drilling samples sealed on site and delivered directly to independent lab Intertek Mineral Limited located in Tarkwa, Ghana for preparation and 50g Fire Assay with AAS finish.

^{5.} QA/QC procedures include industry standard inclusion of standards, blanks, and duplicates in all sample batches.

Newcore Gold Ltd. | Enchi Gold Project

2024 Drill Results

Table accompanies news release dated October 30, 2024



Previously Released Drill Results

Hole ID	Zone/Deposit	From (m)	To (m)	Length (m)	Au (g/t)	UTM East	UTM North	Elevation	Azimuth °	Dip°	Hole Length (m)
KBRC288	Boin	86.0	87.0	1.0	0.85	519558	634796	132	114	-60	201
and		93.0	98.0	5.0	0.47						
and		139.0	201.0	62.0	1.96						
including		139.0	164.0	25.0	2.31						
including		171.0	199.0	28.0	2.23						
KBRC289	Boin	0.0	3.0	3.0	0.17	519608	634766	132	114	-60	151
and		17.0	18.0	1.0	0.25						
and		66.0	77.0	11.0	0.65						
and		97.0	107.0	10.0	1.46						
KBRC290	Boin	33.0	38.0	5.0	0.40	519453	634446	130	114	-60	103
KBRC291	Boin	11.0	17.0	6.0	1.16	519374	634438	132	114	-60	140
and		49.0	50.0	1.0	0.18						
and		56.0	63.0	7.0	0.77						
and		98.0	100.0	2.0	0.27						
and		102.0	103.0	1.0	0.42						
and		118.0	119.0	1.0	1.61						
and		122.0	139.0	17.0	0.56						
KBRC292	Boin	8.0	10.0	2.0	0.30	519415	634419	133	114	-60	110
and		55.0	62.0	7.0	0.50						
KBRC293	Boin	10.0	29.0	19.0	0.46	519452	634401	133	114	-60	101
including		10.0	14.0	4.0	1.28						
including		23.0	28.0	5.0	0.56						
and		33.0	34.0	1.0	0.21						
and		43.0	47.0	4.0	0.62						

^{1.} Intervals reported are hole lengths with true width estimated to be 75 - 85%.

^{2.} Length-weighted averages from uncut assays.

^{3.} All drilling completed by independent contractor.

^{4.} All drilling samples sealed on site and delivered directly to independent lab Intertek Mineral Limited located in Tarkwa, Ghana for preparation and 50g Fire Assay with AAS finish.

^{5.} QA/QC procedures include industry standard inclusion of standards, blanks, and duplicates in all sample batches.